



# Product Specification Data



## Description

BriteLine® Shield gloss overlaminating film is a pressure sensitive 3-mil high gloss PVC film on a smooth paper liner. This laminate offers protection from abrasion, moisture and other environmental exposures. It is laminated by the cold laminating process without the addition of heat.

## Applications

Gloss overlaminating vinyl film is designed to protect digital image prints and screen printed images for exhibit and display graphics. Can be used in most instances where an overlay with a high gloss finish is required.

## Adhesion

To stainless steel 48 oz/in. When tested according to PSTC-1 with 24 hr. dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production

## Thickness

Film	3 mil
Adhesive	.8 to 1.0 mil
Liner	4.0 mil
(Thickness variance $\pm$ 10%)	

## Temperature Ranges

Minimum application temperature is 40°F.  
Service temperature range is -40°F to 180°F.

## Dimensional Stability

Good

## Product Series

OL-GLS30	30" x 150'
OL-GLS38	38" x 150'
OL-GLS54	54" x 150'
OL-GLS61	60" x 150'

## Durability

3 year indoor  
1 year outdoor

### Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions or sale, including disclaimer of warranties and limitation of liability.