

G-FLEX Nylon 800 Series



Special Features

Self-Adhesive PET liner

Designed for difficult fabrics. Suitable to transfer onto Nylon and textiles with hydrophobic impregnation.

Application Instructions

Plotter Settings

Blade: 45°

Cut Style: Cut this material in mirror image

Transfer Conditions

Temperature: 300° F - 305° F

Pressure: Medium pressure (2-2.5 bar)

Time: Pre-Press: 4 seconds

Peel: Lukewarm peel. After cooling down, cover material with a Teflon Sheet and repress for 10 seconds.

Wash Resistance

Warm wash 105° F

Wash garment inside-out

Follow wash instructions for nylon

** Guarantee for a secure and long-lasting bond of G-FLEX NYLON is only given when following the specified temperature and pressure conditions. We recommend evaluation on test material.*

** Metallic colors cannot be on bottom layer*

Available Sizes

15" x 5 yds

15" x 10 yds

15" x 30 yds



45° blade recommended



Medium, even pressure



Warm wash 105° F
Wash garment inside-out
Follow wash instructions
for nylon



Cut this material in mirror image



Pre-press, 4 seconds



300° F - 305° F



Lukewarm peel. After cooling down, cover material with a Teflon Sheet and repress for 10 seconds.



White
801



Navy Blue
805



Yellow
810



Green
804



Orange
815



Forest Green
807



Red
808



Gray
812



Bordeaux
809



Black
802



Purple
814



Gold Metallic
820



Light Blue
803



Silver Metallic
830



Royal Blue
806



Reflex Eco
882

