

Product Specification Data

G-Flex Turbo Print 236



Description

TOP SELLER Briteline® HTV G-Flex Turbo Print 236 is a 3 mil, matte, white, printable heat transfer film equipped with a special hotmelt for fast application at low temperature. The soft, elastic transfer film offers a comfortable textile touch and convinces due to high wearing comfort. G-Flex Turbo Print 236 excels due to an excellent opacity. The raw materials are ecologically inert, do not contain PVC, plasticizers or heavy metals (in accordance with OEKO-TEX STANDARD 100 Class I).

Technical Data

Transfer Film Polyurethane, cast
Adhesive Polyurethane-hotmelt

Thickness 3 m

Liner PET-film, self-adhesive
Suitable substrates Cotton, polyester, polyester/cotton, polyester/acrylic,

uncoated nylon

Finish Matte

Transfer Conditions

Time and Temperature 3 sec at 320° F

4 sec at 300° F 5 sec at 265° F

Pressure 2.5 - 3.0 bar, medium pressure

Nylon Application

Time and Temperature Pre Heat 5 sec.

Apply to Nylon 5 sec.

Remove PET liner, cover transfer with silicon paper & apply for

further 10 sec.

Pressure 2.0 bar, low pressure

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local/national authorities.

Wash Resistance/Printing

Wash resistance 140° F

Suitable for tumble drying and dry-cleaning. Wash textile inside out.

Printing True-sided

Compatibility Solvent, eco-solvent, latex

Recommendations

We recommend evaluation on test material.

Recommended Transfer Tape: Briteline® HTV 854

Statement of Practical Use

We believe the information on this product to be accurate. However, since we cannot anticipate or control the conditions under which this information or our products may be used, we cannot guarantee results obtained through their use. Tests of our products should be made by users to determine the suitability of these products for a specific purpose. The products are sold without warranty, either express or implied. The purchaser should refer to Grimco, Inc's price list for terms and conditions or sale, including disclaimer of warranties and limitation of liability.